

Di-mol 10W30 Scooter

TYPE OF USE: Di-mol 10W30 Scooter is specifically designed engine oil for gearless scooters for which manufacturers recommend the specific grade API-SL/ JASO MB.

PERFORMANCE: Di-mol 10W30 Scooter has the formulation to provide excellent control of piston deposit, wear and corrosion. With good detergency in oil, it maintains the cleanliness and Anti-Oxidant agents prevent premature ageing of oil.

TYPICAL PROPERTIES:

Sr. No	CHARACTERISTICS	TEST METHOD	VALUES
1	SAE viscosity grade	SAE J300	10W30
2	Density @ 15°C	ASTM D4502	0.87
3	Flash Point °C	ASTM D92	216
4	Kinematic Viscosity @ 40°C	ASTM D445	87.11
5	Kinematic Viscosity @ 100°C	ASTM D445	11.23
6	Pour point °C	ASTM D97	-30
7	Total Base Number mg KOH/g	ASTM D2896	7.7
8	Viscosity Index	ASTM D 2270	122

Disclaimer:

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only.