

Di-mol 20W40 CRUISE

TYPE OF USE: Di-mol 20W40 CRUISE is specific engineered engine oil for 4 stroke motorcycle engines fitted with integrated gearbox or wet/dry clutch meeting the emission norms compatible for Indian weather and terrain for which manufacturers recommend the specific grade API-SN/ JASO MA2.

PERFORMANCE: Di-mol 20W40 CRUISE has the formulation to provide excellent control of piston deposit, wear and corrosion. With good detergency in oil, it maintains the cleanliness and Anti-Oxidant agents prevent premature ageing of oil.

TYPICAL PROPERTIES:

| Sr. No | CHARACTERISTICS | TEST METHOD | VALUES |
|--------|-----------------------------|-------------|--------|
| 1 | SAE viscoity garde | SAE J300 | 20W40 |
| 2 | Density @ 15°C | ASTM D4502 | 0.87 |
| 3 | Flash Point °C | ASTM D92 | 222 |
| 4 | Kinematic Viscosity @ 40°C | ASTM D445 | 115.35 |
| 5 | Kinematic Viscosity @ 100°C | ASTM D445 | 17.18 |
| 6 | Pour point °C | ASTM D97 | -30 |
| 7 | Total Base Number mg KOH/g | ASTM D2896 | 7.9 |
| 8 | Viscosity Index | ASTM D 2270 | 125 |

Disclaimer:

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only.