

## Di-mol 20W50 CNG POWER

**TYPE OF USE:** Di-mol 20W50 CNG POWER is specific engineered petrol/cng engine oil for 4 stroke engines meeting the emission norms compatible for Indian weather and terrain for which manufacturers recommend the specific grade API-SM.

**PERFORMANCE:** Di-mol 20W50 CNG POWER has the formulation to provide excellent control of piston deposit, wear and corrosion. With good detergency in oil, it maintains the cleanliness and Anti-Oxidant agents prevent premature ageing of oil.

### TYPICAL PROPERTIES:

Sr. No	CHARACTERISTICS	TEST METHOD	VALUES
1	SAE viscosity grade	SAE J300	20W50
2	Density @ 15°C	ASTM D4502	0.87
3	Flash Point °C	ASTM D92	220
4	Kinematic Viscosity @ 40°C	ASTM D445	140
5	Kinematic Viscosity @ 100°C	ASTM D445	16.2
6	Pour point °C	ASTM D97	-30
7	Total Base Number mg KOH/g	ASTM D2896	9.4
8	Viscosity Index	ASTM D 2270	120

Disclaimer:

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only.