

Di-mol 5W40 ULTRASAFE

TYPE OF USE: Di-mol 5W40 ULTRASAFE is specific engineered engine oil for 4 stroke passenger car engines meeting the emission norms compatible for Indian weather and terrain for which manufacturers recommend the specific grade API-SN/ ILSAC-GF5.

PERFORMANCE: Di-mol 5W40 ULTRASAFE has the formulation to provide excellent control of piston deposit, wear and corrosion. With good detergency in oil, it maintains the cleanliness and Anti-Oxidant agents prevent premature ageing of oil.

TYPICAL PROPERTIES:

Sr. No	CHARACTERISTICS	TEST METHOD	VALUES
1	SAE viscosity grade	SAE J300	5W40
2	Density @ 15°C	ASTM D4502	0.866
3	Flash Point °C	ASTM D92	226
4	Kinematic Viscosity @ 40°C	ASTM D445	83.33
5	Kinematic Viscosity @ 100°C	ASTM D445	11.77
6	Pour point °C	ASTM D97	-24
7	Total Base Number mg KOH/g	ASTM D2896	10.1
8	Viscosity Index	ASTM D 2270	134

Disclaimer:

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only.