

## Di-mol HYDRAPOWER AW 68

**INTRODUCTION** Di-mol HYDRAPOWER AW 68 oils are formulated with premium base oil technology and designed to give robust protection to hydraulic pumps in mobile and stationary systems. These are high viscosity index hydraulic oils that provide a wide operating temperature range.

**FEATURES:** Di-mol HYDRAPOWER AW 68 oils incorporate anti-wear additives, oxidation and corrosion inhibitors, foam and aeration suppressants, and a shear stable viscosity index improver. Hydraulic systems, due to the nature of their operation, experience accelerated wear unless they are protected by clean, high quality anti-wear hydraulic oils. Surging pressures in pumps and valves can increase metal-to-metal contact unless anti-wear protection is present. The anti-wear additives in Di-mol HYDRAPOWER AW 68 oils plate out on the metal surfaces. As hydraulic pressures increase over 1000 psi, the need for anti-wear protection increases proportionally.

### TYPICAL PROPERTIES:

| Sr. No | CHARACTERISTICS             | TEST METHOD | VALUES |
|--------|-----------------------------|-------------|--------|
| 1      | Density @ 15°C              | ASTM D4502  | 0.867  |
| 2      | Flash Point °C              | ASTM D92    | 216    |
| 3      | Kinematic Viscosity @ 40°C  | ASTM D445   | 72.99  |
| 4      | Kinematic Viscosity @ 100°C | ASTM D445   | 11.05  |
| 5      | Pour point °C               | ASTM D97    | -15    |
| 6      | viscosity index             | ASTM D2270  | 142    |
| 7      | Copper corrosion            | ASTM D130   | 1b     |
| 8      | Rust Test                   | ASTM D665   | pass   |

Disclaimer:

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only.